

# Video Inspection

Model: KC-360A-2

## **Operation Manual**



# Video Inspection

**Model: KC-360A-2**

## Overview

KC-360A-2 Video inspection has been designed as a user friendly and economical way of solving hidden problems and increasing productivity. (e.g. Inspect vent pipe and system of air conditioner, machine equipment, engine and so on).

The product has a 2.4 " high resolution color LCD. The camera head is connected to the probe and with adjustable LED lights, which helps you to reach gaps and holes. The camera head has equipped with several accessories, which makes it flexible. The magnetic tip is used to pick up small metal objects. The mirror tip is easy to view the 90° angle. The hook is used to grab onto objects.

KC-360A-2 video inspection features 2 times zooming and picture rotation. It also has the advantages of small size、clear image、stable performance、easy operation and portability. It is widely used in applications such as the industry, the building, the aviation, the vehicles maintenance.

## Technical specifications

Name	Video inspection	
Model	KC-360A-2	
Recommended usage	Indoor	
Viewable angle	60 degrees	
Focal length	50mm	
Depth of view	2.5cm~30cm	
Outer diameter of camera head	Standard	12mm (attachments: magnet, hook and mirror)
	Optional	9mm (attachments: magnet, hook, mirror and screw thread protector)
		5.5mm (attachments: mirror, deflective ball and screw thread protector)
Display	2.4" TFT/LCD	
LCD resolution	320×240 pixel	
Probe length	100cm or customized length	
Probe and camera head ingress protection standard	IP67	
Light source	Ultra high brightness LED	
Power supply	One 9V alkaline battery (6LR61)	
Battery life	Over 2.5hours	
Working temperature	0℃~45℃	
Working moisture	5%~95%RH non-condensing	
Storage	-20℃~+60℃, ≤85% (w/o battery)	
Dimension of device	215mm×156mm×80mm	
Weight	约 218g (w/o battery and probe)	